

EB-Z11005

DATASHEET



The black EB-Z11005 is an impressive and versatile installation projector, with rental applications, that displays images with 11,000 lumens brightness and in XGA resolution. Able to project portrait aspect images for digital signage, the EB-Z11005 has a flexible installation angle, lens shift for off-centre positioning and plenty of calibration options, with optional Wi-Fi and HDBaseT connectivity.

Clear images and 3LCD technology

At 11,000 lumens the EB-Z11005 is an ultra-bright XGA resolution projector. This projector benefits from Epson's 3LCD technology, which ensures high-quality images with equally high White and Colour Light Output for vivid colours and bright images, even in daylight, and three times brighter colours than competitive projectors¹.

Perfect for large venues

Museums, auditoriums and corporate environments can benefit from the EB-Z11005's large projected image, ideal for making a big impact.

Portrait projection

Able to project portrait aspect images, the EB-Z11005 is ideal for digital signage. Welcome to a whole new way of seeing things; portrait mode is also useful when a venue or event, such a fashion show, doesn't lend itself to landscape projection.

Easy set-up

As well as a flexible installation angle and lens shift for off-centre positioning, the EB-Z11005 includes plenty of calibration options such as edge blending, test patterns and Epson's Super Resolution feature.

Connectivity

The EB-Z11005 includes HDBaseT, which allows up to five connections in one. Optional Wi-Fi is also included for extra flexibility.

KEY FEATURES

- **High-brightness**
Ultra-bright at 11,000 lumens
- **Flexible**
Choose different installation angles
- **3LCD technology**
For vivid colours and bright images
- **Connectivity**
HDBaseT and optional Wi-Fi connectivity
- **Portrait projection**
When landscape isn't suitable



EPSON
EXCEED YOUR VISION

PRODUCT SPECIFICATIONS

OPTICAL

Lens Shift	Motorized - Vertical \pm 56 %, horizontal \pm 19 %
Projection Ratio	1,65 - 2,65:1
Zoom	Motorized, Factor: 1 - 1,61
Projection Size	60 inches - 500 inches
Projection Distance Wide	1,9 m - 16,8 m
Projection Distance Tele	3,2 m - 27,2 m
Projection Lens F Number	1,65 - 2,51
Focal Distance	36 mm - 57,5 mm
Focus	Motorized
Lens	Optical

TECHNOLOGY

Projection System	3LCD Technology, RGB liquid crystal shutter
LCD Panel	1,06 inch with C2 Fine

IMAGE

Colour Light Output	11.000 lumen-7.300 lumen (economy)
White Light Output	11.000 lumen - 7.300 lumen (economy)
Portrait Colour Light Output	8.500 lm
Portrait White Light Output	8.500 lm
Resolution	XGA, 1024 x 768, 4:3
Contrast Ratio	15.000 : 1
Lamp	380 W, 2.000 h durability, 4.000 h durability (economy mode)
Lamp (portrait mode)	304 W, 1.000 Hours Durability
Keystone Correction	Manual vertical: \pm 30 °, Manual horizontal \pm 30 °
Aspect Ratio	4:3

CONNECTIVITY

Interfaces	USB 1.1 Type A, USB 2.0 Type B (Service Only), RS-232C, WLAN, Wireless LAN IEEE 802.11b/g/n (optional), VGA in, VGA out, DVI in, HDMI in, Composite in, Component in, BNC in (6x), S-Video in, HDBaseT
------------	--

ADVANCED FEATURES

Security	Kensington lock, Security cable hole
Video Colour Modes	Dynamic, Photo, Presentation, sRGB, Theatre, DICOM SIM

GENERAL

Energy Use	1.060 W, 788 W (economy), 0,37 W (standby)
Product dimensions	741 x 534 x 197 mm (Width x Depth x Height)
Product weight	26 kg
Noise Level	Normal: 40 dB (A) - Economy: 35 dB (A)
Included Software	EasyMP Monitor, EasyMP Multi PC Projection, EasyMP Network Projection
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Temperature	Storage -10° C - 60° C
Humidity	Operation 20% - 80%, Storage 10% - 90%
Options	Document camera, Quick wireless USB key, Wireless LAN unit

OTHER

Warranty	36 months Carry in or 20.000 h, Lamp: 12 months or 1.000 h
----------	--

LOGISTICS INFORMATION

SKU	V11H606140
Barcode	8715946541235
Dimensions Single Carton	657 x 903 x 364 mm
Carton Weight	33,95 Kg
Country of Origin	Multiple country of origin

EB-Z11005

WHAT'S IN THE BOX

- Computer cable
- HDMI Cable Clamp
- Power cable
- Remote control incl. batteries
- User's Manual Set

OPTIONAL ACCESSORIES

- Lamp - ELPLP82 - EB-Z9xxx/Z1000xU/Z11xxx (x2) V13H010L82
- Lamp - ELPLP81 - EB-Z9xxx/Z1000xU/Z11xxx V13H010L81
- 3D Polarizer - ELPLL01 - G6xxx / 48/4950 / Z9/11xxx / Z1000xU V12H618A01
- Adapter - ELPAP07 Wireless LAN b/g/n V12H418P13ZA
- Ceiling Mount - ELPMB25 Low EB-Z8xxx V12H003B25
- Ceiling Mount - ELPMB26 High EB-Z8xxx V12H003B26
- HDBaseT Transmitter - ELPHD01 V12H547040
- Passive 3D Glasses for Child (x5) - ELPGS02B V12H541B10
- Quick Wireless Connect USB key - ELPAP09 V12H005M09

OPTIONAL LENSES

- Lens - ELPLU02 - EB-Z9xxx/Z1000xU/Z11xxx ST Off Axis V12H004U02
- Lens - ELPLL07 - EB-Zxxx Long Throw V12H004L07
- Lens - ELPLM06 - EB-Zxxx Middle Throw1 V12H004M06
- Lens - ELPLM07 - EB-Zxxx Middle Throw2 V12H004M07
- Lens - ELPLR04 - EB-Zxxx Rear Wide V12H004R04
- Lens - ELPLW04 - EB-Zxxx Wide V12H004W04

1. Compared to leading 1-chip DLP business and education projectors based on NPD data, July 2011 through June 2012. Colour brightness (Colour Light Output) measured in accordance with IDMS 15.4. Colour brightness will vary depending on usage conditions. For more information please visit www.epson.eu/CLO

EPSON[®]