

# EB-525W



## DATASHEET



The EB-525W delivers superior-quality images and a host of additional features as standard to give users more for their money. Ideal for classrooms or small meeting rooms, this projector can be wall or ceiling mounted or placed on a table close to the wall to free-up more workspace.

### High-quality image

Complete with our 3LCD technology, the EB-525W displays superior-quality, bright images with more accurate colours. The image can be seen even in brightly-lit rooms thanks to an equally high white and colour light output. Image detail is clear thanks to a high contrast ratio and our new short throw lens means sharper images and improved focus.

### More value for your money

The lamp in the EB-525W now lasts up to 10,000 hours in eco mode. The projector even conserves power during presentations by automatically adjusting the light output depending on the content. The A/V mute function pauses the presentation and dims the lamp by 70% to conserve energy while the projector is not in use. The projectors' built-in 16w speaker means audio content can be played directly through the projector, without the need for additional external speakers. The microphone input transforms the projector into a PA system, meaning presenters can be easily heard in a classroom environment.

### Easy to set up and use

The EB-525W has both horizontal and vertical keystone correction to achieve a perfectly shaped image and help avoid distortion. When setting up several projectors, the OSD settings can be copied from one projector to many others meaning you don't need to set up projectors individually. Multi-PC projection software allows content from four devices, including PC's, tablets, smart phones, to be displayed simulatenously.

## KEY FEATURES

- **Exceptional image quality**  
Epson's 3LCD technology displays brighter images and more accurate colours
- **Equally high white and colour light output**  
Projected image can be seen clearly even in brightly-lit rooms
- **Clearer detail**  
Increased contrast ratio of 16,000:1
- **Longer lamp life means low TCO**  
10,000 hours in eco mode / 5,000 hours in normal mode
- **Flexible installation options**  
Horizontal and vertical keystone correction for off-centre and uneven placement



**EPSON**<sup>®</sup>  
EXCEED YOUR VISION

## PRODUCT SPECIFICATIONS

### IMAGE

|                          |   |
|--------------------------|---|
| Colour Light Output      | 2.800 lumen-1.700 lumen (economy)                                     |
| White Light Output       | 2.800 lumen - 1.700 lumen (economy) In accordance with ISO 21118:2012 |
| Resolution               | WXGA, 1280 x 800, 16:10   |
| Lamp                     | 200 W, 5.000 h durability, 10.000 h durability (economy mode)         |
| Keystone Correction      | Manual vertical: $\pm 15^\circ$ , Manual horizontal $\pm 15^\circ$    |
| Colour Reproduction      | Upto 1.07 billion colours   |
| Contrast Ratio           | 16.000 : 1  |
| High Definition          | HD ready  |
| Aspect Ratio             | 16:10   |
| Colour Processing        | 10 Bits   |
| 2D Vertical Refresh Rate | 50 Hz - 85 Hz   |

### OPTICAL

|                          |                           |
|--------------------------|---------------------------|
| Projection Ratio         | 0,48:1                    |
| Projection Size          | 53 inches - 116 inches    |
| Zoom                     | Digital, Factor: 1 - 1,35 |
| Projection Distance Wide | 0,5 m (53 inch screen)    |
| Projection Distance Tele | 1,2 m (116 inch screen)   |
| Projection Lens F Number | 1,6                       |
| Focal Distance           | 6,4 mm                    |
| Focus                    | Manual                    |
| Offset                   | 9,51 : 1                  |
| Lens                     | Optical                   |

### CONNECTIVITY

|                       |   |
|-----------------------|---|
| Interfaces            | USB 2.0 Type A, USB 2.0 Type B, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11b/g/n (optional), VGA in (2x), VGA out, HDMI in, Composite in, Component in (2x), S-Video in, Stereo mini jack audio out, Stereo mini jack audio in (2x), Microphone input, Cinch audio in |
| USB Display Function  | 3 in 1: Image / Mouse / Sound   |
| Epson iProjection App | Ad-Hoc / Infrastructure   |

### GENERAL

|                    |   |
|--------------------|---|
| Noise Level        | Normal: 35 dB (A) - Economy: 29 dB (A)  |
| Loudspeaker        | 16 W  |
| Energy Use         | 278 W, 219 W (economy), 0,28 W (standby)  |
| Product dimensions | 344 x 315 x 94 mm (Width x Depth x Height)  |
| Product weight     | 3,9 kg  |
| Included Software  | EasyMP Monitor, EasyMP Multi PC Projection, EasyMP Network Projection   |
| Supply Voltage     | AC 100 V - 240 V, 50 Hz - 60 Hz   |
| Temperature        | Operation $5^\circ\text{C}$ - $35^\circ\text{C}$ , Storage $-10^\circ\text{C}$ - $60^\circ\text{C}$                             |
| Humidity           | Operation 20% - 80%, Storage 10% - 90%  |
| Options            | Connection and control box, Document camera, Quick wireless USB key, Short throw wall mount, Soft carry case, Wireless LAN unit |

### OTHER

|          |   |
|----------|---|
| Warranty | 24 months Carry in, Lamp: 12 months or 1.000 h<br>Optional warranty extension available |
|----------|---|

## LOGISTICS INFORMATION

|                          |                    |
|--------------------------|--------------------|
| SKU                      | V11H672040         |
| EAN code                 | 8715946541464      |
| Dimensions Single Carton | 504 x 386 x 209 mm |
| Carton Weight            | 5,6 Kg             |
| Multiple Order Quantity  | 1 Units            |
| Country of Origin        | China              |

## EB-525W

### WHAT'S IN THE BOX

- Computer cable
- Main unit
- Power cable
- Remote control incl. batteries
- Setup guide
- Software (CD)
- User manual (CD)

### OPTIONAL ACCESSORIES

- Active Speakers - ELPSP02  
V12H467040
- Ceiling Mount - ELPMB23 - White  
V12H003B23
- Ceiling pipe - ELPFP13 - 668-918mm  
V12H003P13
- Ceiling pipe - ELPFP14 - 918-1168mm  
V12H003P14
- Quick Wireless Connect USB key - ELPAP09  
V12H005M09
- Air Filter - ELPAF47 - EB-52x / EB-53x  
V13H134A47
- Lamp - ELPLP87 - EB-52x / 53x (215W)  
V13H010L87
- Wall Mount - ELPMB45 - ST EB52x/53x  
V12H706040
- Control and Connection Box - ELPCB02  
V12H614040

